



400 Barrel Portable Tanks

## 40 Years of Manufacturing Experience



Over 175,000 sq ft of combined manufacturing facilities.

Baked on Zinc Rich Epoxy Powder –Super Durable Powder Coat Finish - Chemical Resistant Liners (above)



Powder Coat Ovens (Max Dimension - 60'x24'x19') (right)

# **400 Barrel Portable Tanks**

#### **Features & Options**

#### **Features:**

- Shell 12' dia. x 20' high (3/16")
- Sloped Bottom 12" slope (1/4")
- Coned Roof (3/16")
- Roof Manway (24"x36")
- Centre roof vent plug (4" NPT)
- Side Wall Manway (24"x36")
- L-Skid 5-8"MF; 3-6"WF & 4" roll ends
- Tow Sling (7/8" x 15')
- Ladder 5/8" sq. rotated 45 degrees, inserted into side rails
- Toe Rail (6" high)
- Level indicator c/w float & decal
- 4" 150 ANSI RFSO Flanges c/w flanges and plugs
- 4" Butterfly Valves
- 4" Down Comer (180 degree off roof)
- Thief Hatch
- Name Plate (specifications)
- Baked on Powder Coat Finish
- Built to API 12F modified
- Air Tested to A.P.I. Spec

### **Options:**

- Double Wall
- Interior Blast
- Tank Liners (chemical resistant)
- Steam Coil 22' of 2" schedule 80
- Bolt on safety rings at top of ladder
- Bolt on ladder cage
- Amgas Sealed Sour Service level indicator c/w float & decal
- Sour Service Thief Hatch
- Decals (supplied by customer or customer made)
- Custom options available on larger quantity orders